Chunghwa Picture Tubes, Ltd.
Technical Specification

To : SCL

Date : 2011/08/01

TFT LCD
CLAA156WB13A

APPROVED BY	CHECKED BY	PREPARED BY
Ronald Huang	Alan Shih	Carol Shen

Prepared by :

FAE Division

VD Business Unit

CHUNGHWA PICTURE TUBES, LTD.

1127 Hopin Rd., Padeh, Taoyuan, Taiwan 334, R.O.C.
TEL: +886-3-3675151   FAX: +886-3-377-3003

Doc.No:	CLAA156WB11A-Wistron-V1-2011/02/12	Issue Date:	2011/02/12

REVISION STATUS

Revision Notice	Description	Page	Rev. Date
V1	Final spec.	-	2011/08/01

Table of Content

1. OVERVIEW

CLAA156WB13A is 15.6" color (16：9) TFT-LCD (Thin Film Transistor Liquid Crystal Display) module composed of LCD panel, LVDS driver ICs, control circuit and backlight. By applying 6 bit digital data, 1366×RGB (3) ×768, 262K-color images are displayed on the 15.6" diagonal screen. General specifications are summarized in the following table：

ITEM	SPECIFICATION
Display Area	344.232(H) x 193.536(V) (mm) (15.6-inch diagonal)
Number of Pixels	1366 x 3 (RGB) x 768
Pixel Pitch	0.252(H) x 0.252(V) (mm)
Color Pixel Arrangement	RGB vertical stripe
Display Mode	Normally white
Number of Colors	262,144(6bits) (LVDS)
Gamut	56%(min)/60% (Typ)
Optimum Viewing Angle	6 o'clock
Response Time	16ms (Typ)
Surface Treatment	Glare
Viewing Angle	40°、-40° /15°、-30° (MIN.)
Brightness	220 cd/m^2 (5point) (Typ)
Uniformity	5point：80%
Consumption of Power	5W (Max)
Module Size	359.8(W)×210(H)×5.5(D) (mm)（Max）
Module Weight (g)	450 g (Max)

The LCD Products listed on this document are not suitable for use of aerospace equipment, submarine cable, and nuclear reactor control system and life support systems. If customers intend to use these LCD products for applications listed above or those not included in the "Standard" list as follows, please contact our sales in advance.

Standard：Computer, Office equipment, Communication equipment, Test and Measurement equipment, Machine tool, Industrial robot, Audio and Visual equipment, Other consumer products.

CPT   CHUNGHWA PICTURES TUBES, LTD.,

2. ABSOLUTE MAXIMUM RATINGS

The following are maximum value, which if exceeded, may cause faulty operation or damage to the unit.

ITEM	SYMBOL	MIN	MAX	UNIT	NOTE
LCD Power Voltage	VCC	0	4.0	V	
LED Driver Input Voltage	VBL+	7	21	V	
Operation Temperature	Top	0	50	℃	*1).*2).*3).*4).
Storage Temperature	Tstg	-25	65	℃	*1).*2).*3).

【Note】

*1) The relative temperature and humidity range are as below sketch, 90%RH Max. (Ta≦40℃)

*2) The maximum wet bulb temperature ≦39℃(Ta＞40℃) and without dewing.

*3) If product in environment which over the definition of the relative temperature and humidity out of range too long, it will affect visual of LCD.

*4) If you operate LCD in normal temperature range, the center surface of panel should be under 50℃.

3. ELECTRICAL CHARACTERISTICS

(A) TFT LCD

ITEM		SYMBOL	MIN	TYP	MAX	UNIT	NOTE
LCD Power Voltage		VCC	3.0	3.3	3.6	V	*1)
LCD Power Current		ICC	-	303	333	mA	*2)
Rush Current		Irush	-	-	2	A	*4)
Logic Input Voltage (LVDS: IN+,IN-)	Common Voltage	VCM	1.125	1.25	1.375	V	*3)
	Differential Input Voltage	｜VID｜	250	350	450	mV	*3)
	Threshold Voltage (HIGH)	VTH	-	-	100	mV	*3) When VCM = +1.2V
	Threshold Voltage (LOW)	VTL	-100	-	-	mV	

【Note】

*1) Power Sequence：

0.50 ms≦t1 ≦10 ms   500 ms≦t4
0.01 ms＜t2 ≦50 ms   200 ms≦t5
0.01 ms＜t3 ≦50 ms   200 ms≦t6

data:RGB DATA, DCLK, HD, VD, DENA

VCC-dip state

(1)when 3.0V＞VCC≧2.7V，td≦10 ms.

(2)when VCC＜2.7V，VCC-dip condition should as the VCC-turn-off condition.

Vin=3.3V

2.7V 3.0V

td

*2) Typical value is Mosaic (32*36 Checker board) Pattern：768 line mode.

Circuit condition (Typ)：VCC=3.3 V，f_V=60 Hz f_H=48.36 kHz，f_{CLK}=75.44 MHz

Max value is Black Pattern：768 line mode.

Circuit condition (Max)：VCC=3.3 V，f_V=60 Hz f_H=48.36 kHz，f_{CLK}=75.44 MHz

.

CPT　　　　　　　　　　　　　　　　　　　CHUNGHWA PICTURES TUBES, LTD.,

*3) LVDS Signal Definite：

VIN+：Positive differential DATA & CLK Input
VIN-：Negative differential DATA & CLK Input

*4) Irush measure condition

(B) BACK LIGHT

(a.) ELECTRICAL CHARACTERISTICS

Ta=25℃

ITEM	SYMBOL	MIN	TYP	MAX	UNIT	NOTE
LED Driver Input Voltage	VBL+	7	12	21	V	
LED Driver Input Current	IBL+			650	mA	*1)
Forward Voltage	V_F	2.9	3.2	3.5	V	*2) I_F=20mA
Forward Current	I_F	19.5	20	20.5	mA	*2)
Power Consumption	PLED	-	3.614	3.953	W	*2)*3) I_F=20mA
PWM Frequency	PWM_BL	180	200	1k	Hz	*2)I_F=20mA
Duty ratio	Dim	5		100	%	

(b.) LED LIFE – TIME

ITEM	CONDITION	MIN	TYP	MAX	UNIT	NOTE
Life Time	I_F=20mA 、Ta=25℃	15000			hrs	*4)

(c.) LED ON/OFF Sequence：

10ms ≦ T1　　　　0ms ≦ T3

10ms ≦ T2　　　　10ms ≦ T4

*1) Maximum LED Driver Input Current at 7V Input Voltage/PWM Duty 100%.

*2) Measure method：a. LED current is measured by utilizing a current meter as show below.

b. System power PLED is measured at input voltage 12V.

PLED

| B/L unit | | LED Driving Circuit | | System Power |

A

*3) Calculator value for reference $I_F \times V_F \times N = PLED$

*4) Life time means that estimated time to 50% degradation of initial luminous intensity.

4. Connector Interface PIN & Function

CN (Interface signal)

Outlet connector: 5-2069716-3 (TYCO) or compatible

| Pin No.	SYMBOL	FUNCTION
1	NC	No connection
2	VDD	Power Supply, 3.3 V (typical)
3	VDD	Power Supply, 3.3 V (typical)
4	V EEDID	DDC 3.3V power
5	NC	No connection
6	Clk EEDID	DDC Clock
7	DATA EEDID	DDC Data
8	Odd_Rin0-	- LVDS differential data input (R0-R5, G0) (odd pixels)
9	Odd_Rin0+	+ LVDS differential data input (R0-R5, G0) (odd pixels)
10	VSS	Ground – Shield
11	Odd_Rin1-	- LVDS differential data input (G1-G5, B0-B1) (odd pixels)
12	Odd_Rin1+	+ LVDS differential data input (G1-G5, B0-B1) (odd pixels)
13	VSS	Ground – Shield
14	Odd_Rin2-	- LVDS differential data input (B2-B5, HS, VS, DE) (odd pixels)
15	Odd_Rin2+	+ LVDS differential data input (B2-B5, HS, VS, DE) (odd pixels)
16	VSS	Ground – Shield
17	Odd_ClkIN-	- LVDS differential clock input (odd pixels)
18	Odd_ClkIN+	+ LVDS differential clock input (odd pixels)
19	NC	No connection
20	NC	No connection
21	NC	No connection
22	NC	No connection
23	NC	No connection
24	NC	No connection
25	NC	No connection
26	NC	No connection
27	NC	No connection
28	NC	No connection
29	NC	No connection
30	NC	No connection
31	VSSLED	Ground – LED
32	VSSLED	Ground – LED
33	VSSLED	Ground – LED
34	NC	No connection
35	PWM	System PWM Signal Input (+3.3V Swing)
36	LED_EN	LED enable pin (+3.3V Input)
37	NC	No connection
38	VDDLED	7V – 21V LED power
39	VDDLED	7V – 21V LED power
40	VDDLED	7V – 21V LED power

5. INTERFACE TIMING CHART

(1)(a). LVDS input time sequence

Horizontal sequence

(b) LCD input time sequence

(2) Timing Chart

ITEM				SYNBOL	MIN	TYP	MAX	UNIT
LCD Timing	Frame Rate			-	--	60	--	Hz
	DCLK		Frequency	f_{CLK}	65.93	75.44	80.00	MHz
			Period	t_{CLK}	11.26	13.25	15.17	ns
	DENA	Horizontal	Horizontal total time	t_H	1498	1560	1667	t_{CLK}
			Horizontal Active time	t_{HA}	1366	1366	1366	t_{CLK}
			Horizontal Blank time	t_{HB}	132	194	301	t_{CLK}
		Vertical	Vertical total time	t_V	800	806	870	t_H
			Vertical Active time	t_{VA}	768	768	768	t_H
			Vertical Blank time	t_{VB}	32	38	102	t_H
LVDS spread spectrum range *3)					-2		2	%

【Note】

*1) DENA (DATA ENABLE) usually is positive.

*2) During the whole blank period, DCLK should keep input.

*3) LVDS input clock is 85MHz and modulation rate is fixed 100KHz.

*4) MAX set conditions: H-total / V-total can not set the max for the same time

(3) DATA mapping

| Color	Input Data	R DATA						G DATA						B DATA					
		R5 MSB	R4	R3	R2	R1	R0 LSB	G5 MSB	G4	G3	G2	G1	G0 LSB	B5 MSB	B4	B3	B2	B1	B0 LSB
Basic Color	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red(63)	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Green(63)	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
	Blue(63)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1
	Cyan	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1
	Magenta	1	1	1	1	1	1	0	0	0	0	0	0	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
RED	RED(0)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	RED(1)	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0
	RED(2)	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0
	RED(62)	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0
	RED(63)	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
Green	Green(0)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Green(1)	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0
	Green(2)	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0
	Green(62)	0	0	0	0	0	0	1	1	1	1	1	0	0	0	0	0	0	0
	Green(63)	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
Blue	Blue(0)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Blue(1)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
	Blue(2)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
	Blue(62)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	0
	Blue(63)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1

【Note】

1) Gray level:

Color(n)：n is level order; higher n means brighter level.

2) DATA:

1: high，0: low

6. BLOCK DIAGRAM

7. MECHANICAL SPECIFICATION

(1) Front side

The tolerance, not show in the figure, is ±0.5 mm.　　　　　　　　　　　[Unit：mm]

CPT　　　　　　　　　　　　　　　　　CHUNGHWA PICTURES TUBES, LTD.,

(2) Rear side

The tolerance, not show in the figure, is ±0.5 mm.　　　　　　　　　　**[Unit：mm]**

8. OPTICAL CHARACTERISTICS

Ta=25℃，VDD=3.3V

ITEM		SYMBOL	CONDITION	MIN	TYP	MAX	UNIT	NOTE
Contrast Ratio		CR	θ＝ψ＝0°	500	600		--	*1) 2)
Luminance (5P)		L	θ＝ψ＝0°	200	220		cd/m^2	*1) 3)
Uniformity(5P)		ΔL	θ＝ψ＝0°	80			%	*1) 3)
Response Time		Tr	θ＝ψ＝0°		6	9	ms	*5)
		Tf	θ＝ψ＝0°		10	16	ms	*5)
Cross Talk		CT	θ＝ψ＝0°			1	%	*6)
View Angle	Horizontal	ψ	CR≥10	40/-40			°	*4)
	Vertical	θ		15/-30			°	*4)
Color Temperature Coordinate	W	X	θ＝ψ＝0°	0.293	0.313	0.333		*3)
		Y		0.309	0.329	0.349		
	R	X		0.590	0.620	0.650		
		Y		0.310	0.340	0.370		
	G	X		0.300	0.330	0.360		
		Y		0.540	0.570	0.600		
	B	X		0.120	0.150	0.180		
		Y		0.030	0.060	0.090		
Gamut			θ＝ψ＝0°	56%	60%			
Gamma		γ	GL	2.0	2.2	2.4		*7)

Color coordinate and color gamut are measured by SRUL1R, response time is measured by TRD-100, and all the other items are measured by BM-5A (TOPCON). All these items are measured under the dark room condition (no ambient light).

Measurement Condition: IL= 20mA (each LED)

Definition of these measurement items is as follows:

*1) Setup of Measurement Equipment

　　The LCD module should be turn-on to a stable luminance level to be reached. The measurement should be executed after lighting Backlight for 20 minutes and in a dark room.

*2) Definition of Contrast Ratio

　　CR=ON (White) Luminance/OFF (Black) Luminance

***3) Definition of Luminance and Luminance uniformity**

Central luminance: The white luminance is measured at the center position "5" on the screen, see Fig.1 below.

5P Luminance (AVG): The white luminance is measured at measuring points 5、10、11、12、13, see Fig.1 below.

5P Uniformity: $\Delta L = (Lmin / Lmax) \times 100\%$

*4) Definition of view angle(θ，ψ)

Upper (+)

θ   ψ

Left (-)
Gate Drive Side

Right (+)

LCD Panel

Lower (-)

*5) Definition of response time

White

90 %   90 %

Luminanc

10 %   10 %

tr   tf

Black

***6) Crosstalk Modulation Ratio：**

CT=│Y_B-Y_A│/Y_A×× 100%

Y_A、Y_B measure position and definition

Y_A means luminance at gray level 31(exclude gray level 0 pattern)

Y_B means luminance at gray level 31(include gray level 0 pattern)

(0, 0) Active Area

$Y_{A, U}$ (D/2,W/8)

$Y_{A, L}$ (D/8,W/2)   Gray 31 $Y_{A, R}$ (7D/8,W/2)

$Y_{A, D}$ (D/2,7W/8)

(D,W)

(0, 0) Active Area

$Y_{B, U}$ (D/2,W/8)

(D/4,W/4)

$Y_{B, L}$ (D/8,W/2)   Gray 0 $Y_{B, R}$ (7D/8,W/2)

(3D/4,3W/4)

$Y_{B, D}$ (D/2,7W/8)   Gray 31

(D,W)

*7) Definition of Gamma (VESA)

Based on Customer Sample, take the average value as a standard center value and the variation range of gamma value caused by loop voltage error should be between +/- 0.2. the bellow figure shows how to obtain the gamma curve and γ (from gray level: 0、4、8-----60、63).

$$y = \gamma x - k$$

LOG(ΔY)

LOG（Gray Level）

9. RELIABILITY TEST CONDITIONS

(1) Temperature and Humidity

TEST ITEMS	CONDITIONS
High Temperature Operation	50°C ；250Hrs
High Temperature Storage	65°C ；250Hrs
High Temperature High Humidity Operation	40°C ；95％ RH；250Hrs
High Temperature High Humidity Storage	60°C ；90％ RH；48 Hrs
Low Temperature Operation	0°C ；250 Hrs
Low Temperature Storage	-30°C ；250 Hrs
Thermal Shock	-40°C (0.5 Hr)～65°C (0.5 Hr), Ramp<20°C , 100 CYCLES
Temperature & Pressure Storage	-30°C ；260hPa，24 Hrs

(2) Shock & Vibration

TEST ITEMS	CONDITIONS
Shock (Non-Operation)	210G, 3ms, half sine wave, ± X,± Y,± Z 1time each
Vibration (Non-Operation)	Vibration level : $14.7m/s^2$ (1.5G), sinusoidal wave (each x, y, z axis : 1hr, total 3hrs) Frequency range : 5～500 Hz Sweep speed : 0.5 Octave/min.

(3) ESD

	Surface discharge(Panel display area、Frame、PWB、Panel back side)		Electrics capacity of Connector
	Contact	Air	Contact
Capacity	150 pF	150 pF	200 pF
Resistance	330 Ω	330 Ω	0 Ω
Voltage	±8kV	±15kV	±250 V
Interval	1 sec	1 sec	1 sec
Times(single point)	25	25	1

(4) MTBF without B/L: 200,000 Hrs (min) lifetimes.

(5) Judgment standard

The judgment of the above test should be made as follow:

Pass：Normal display image with no obvious non-uniformity and no line defect.

Partial transformation of the module parts should be ignored.

Fail：No display image, obvious non-uniformity, or line defects.